

# Mckinney

CONTAINERS  
Rentals & Sales

## -GENERATORS-



### Mckinney Containers offers Generators

- Competitive Rates
- Daily, Weekly and Monthly Terms
- Portable power
- Restaurants, Hospitals, & Construction
- Prime or Stand-by
- Available in

**Texas & Washington**

#### Reliable:

- Advanced microprocessor
- Voltage regulation within +/- 1%
- Models with full load run times in excess of 24 hours
- Air filter condition indicator
- Low coolant shutdown

#### Tough:

- Aluminum, lockable enclosure
- Steel skid frame and trailer
- Durable industrial powder coat finish
- Stainless steel exterior hardware

#### Easy to Use:

- Voltage selector switch
- Lugs and lug box safety switch
- Multiple convenience outlets
- External emergency stop switch
- External, lockable fuel cap
- Automatic remote start
- Detachable generator-set and trailer
- Fuel tank intergrated into generator-set

#### Seattle, WA Contacts:

Greg Corwin  
800-850-3588 or 253-518-0369  
gregc@mckinney-sea.com

#### Aaron Norlin

800-850-3588 or 253-518-0374  
aaronn@mckinney-sea.com

#### Houston, TX Contacts:

Greg Corwin  
800-850-3588 or 713-797-2811  
gregc@mckinney-hou.com

Model	MMG 25	MMG 45	MMG 55
<b>Output</b>			
3 Phase – Standby (kW/kVA)	20/25	35/44	50/63
Amps (480/208 V)	30/69	53/122	76/175
3 Phase – Prime (kW/kVA)	18/23	33/41	47/59
Amps (480/208 V)	28/64	49/114	71/164
1 Phase – Standby (kW/kVA)	16/16	33/33	49/49
Amps (240 V)	67	138	204
1 Phase – Prime (kW/kVA)	15/15	30/30	46/46
Amps	63	125	192
AC Voltage 1-phase	120, 139, 208, 220, 240, 277		
AC Voltage 3-phase	208, 220, 440, 480		
Frequency Hz	60	60	60
Power Factor	1.0 (1 Phase)/0.8 (3 Phase)		
Generator (Brand/Type/Insulation)	Marathon / Brushless / H		
Sound (dB(A) 23 feet @ prime)	66	68	68
<b>Size and Weight</b>			
Skid Mounted (l x w x h) in	95 x 35 x 52	95 x 35 x 52	95 x 35 x 52
Dry Weight lb (kg)	1738 (788)	2383 (1081)	2450 (1111)
Operating Weight lb (kg)	2206 (1001)	3146 (1427)	3213 (1457)
Trailer Mounted (l x w x h) in	150 x 57 x 67	150 x 57 x 67	150 x 57 x 67
Dry Weight lb (kg)	2258 (1024)	2898 (1315)	2970 (1347)
Operating Weight lb (kg)	2721 (1234)	3661 (1661)	3733 (1693)
Engine	Interim tier IV	Interim tier IV	Tier III
Brand	Isuzu	Kubota	John Deere
Model #	4LENYGV-01	V3600-T-E3BG	PE4024HF285
Asperation	Natural	Turbo	Turbo
HP (prime @ 1800rpm) (kW)	32 (24)	53 (39)	72 (54)
Displacement in3 (L)	134 (2.2)	221 (3.6)	149 (2.4)
Cylinders	4	4	4
Speed (rpm)	1800	1800	1800
Fuel consumed prime gph (Lph)	1.8 (6.8)	3.0 (11.4)	3.6 (13.6)
Battery (12 volt)	1 – 12V / 720 CCA		
<b>Capacities</b>			
Fuel Tank gal (L)	106 (401)	106 (401)	106 (401)
Approximate Run Time hrs	45.4	31	29
<b>AC Distribution</b>			
Main Breaker	90	200	225
Voltage Selection	3 Position Switch (Lockable)		
Voltage Regulation	+ / - 1%	+ / - 1%	+ / - 1%
120V – 20 amp GFCI Duplex	2	2	2
240V – 30 amp Twist Lock	NA	NA	NA
240V – 50 amp Twist Lock	2	2	2
<b>Trailer</b>			
Number of Axles & Capacity lbs (kg)	1 - 3500 (1588)	1 - 5000 (2268)	1 - 5000 (2268)
Tire size (in)	15	15	15
Brakes	None	Surge	Surge
Hitch – Standard	2" Ball	2" Ball	2" Ball